



grandMA3 onPC command wing

Art.-No. 4010511



When we talk about onPC solutions, we talk about mobility, flexibility and affordable prices - all combined in the grandMA3 onPC command wing! It is your mobile control solution for the grandMA3 onPC software.

You have a computer or laptop with the grandMA3 onPC software installed? Then simply connect the grandMA3 onPC command wing via USB and you are ready for programming. The command area looks the same as on the grandMA3 consoles including the five dual-encoders and 40 separate playbacks to directly control 2 048 parameters.

You have three DMX ports available, and you can use Ethernet protocols to send DMX data. On the rear panel you find all inputs and outputs of a grandMA3 console. MIDI, timecode and remote control are directly available. So you get the real console feeling!

The grandMA3 onPC command wing is designed as a powerful control solution on tour, for smaller theaters, shows, clubs or houses of worship. Also, if you are looking for a clever backup solution for your grandMA3 system or if you need a small pre-programming station, the grandMA3 onPC command wing will be the perfect choice.

Do not forget the behaviour of grandMA3 onPC solutions - just add any grandMA3 onPC product to your system to get the maximum count of 4 096 parameters and additional DMX outputs.



Features

- Real-time control for 2 048 parameters in combination with grandMA3 onPC
- Expandable up to 4 096 parameters with onPC products and grandMA3 onPC
- Command section similar to grandMA3 compact layout
- 29 rotary RGB backlit encoder
- 5 dual encoders
- 10 motorized 60 mm faders
- 40 separate playbacks
- 16 assignable x-keys
- 2 motorized A/B faders 100 mm
- 1 Level-Wheel
- Individually backlit and dimmable silent (clickless) keys
- Just connect via USB to any PC running grandMA3 onPC

Scope of delivery

Art.-No.	Article	Quantity
4011454	Dust cover grandMA3 onPC command wing / XT	1
4021426	MA cable USB 2.0, type A to type B, length 2.0m	1
4011387	MA Magnetic plate for easy labeling of 10 faders, for grandMA3	1
4023136	MA Quick Manual for grandMA3 onPC command wing	1

1 x MA power cable, IEC-C plug (lockable), length 2.0 m, open end

Technical Specifications

Parameters	2 048 (HTP/LTP)
Parameters Mode2	not applicable (no Mode2)
Operating voltage/ Supply voltage	AC 100 - 240 V; 50/60 Hz
Power	max. 50 VA
Operating Temperature	0 °C up to 40 °C / 32 °F up to 104 °F
Dimensions	620 x 427 x 102 mm / 25 x 17 x 4 in (width x depth x height)
Net weight	10 kg / 22 lbs
Connectors	1 x IEC-60320 C14 cord 2 x DMX512-A Out (5pin XLR female) 1 x DMX512-A In (5pin XLR male) 1 x MIDI In (5pin DIN female) 1 x MIDI Out (5pin DIN female) 1 x Linear Timecode (3pin XLR female) 1 x GPI General Purpose Interface (D-SUB DE9 female) for remote control 1 x USB 2.0 (type B) 1 x LED desk light (4pin XLR female)

Article

Art.-No.	Article
4010511	grandMA3 onPC command wing



Accessories

Art.-No.	Article
4023468	MA Case grandMA3 onPC command wing, (by Peli)
4022579	MA Case grandMA3 onPC command wing, (by Amptown)
4023575	grandMA3 onPC fader wing
4011080	MA LED desk light grandMA3, straight plug XLR 4pin, length 27", incl. cover
4011081	MA dust cover for LED desk light, 27"

More product pictures

